

Characteristic:

Safety lock buckle, easy installation, screw terminal output.

Product picture printing is for reference only,
subject to the actual product


Technical index:

- Mounting type:Free hanging (In-Line)
- Material of core: Laminated silicon steel
- Applicable standard:: GB20840-2014
- Operating temperature: -25℃ ~ +60℃
- Storage temperature: -30℃ ~ +90℃
- Frequency range: 50Hz-60Hz
- Waterproof grade: IP00
- Dielectric strength: 3.5KV 50Hz 1min



Electrical parameters:The following parameters are typical values. The actual values shall be subject to the actual measurement of the product

Rated input	50		100		200			300		400			A
Rated output	50	100	50	100	20	50	100	50	100	50	80	100	mA
Turns ratio	1:1000	1:500	1:2000	1:1000	1:10000	1:4000	1:1000	1:6000	1:3000	1:8000	1:5000	1:4000	—
Accuracy	0.5	1	0.5/0.2	0.5	0.5/0.2	0.5/0.2	0.5	0.5/0.2	0.5/0.2	0.5/0.2	0.5/0.2	0.5/0.2	%
Sampling resistance	20	10	20	10	50	20	10	20	10	20	20	8	Ω
Weight	204												g



TVS: Transient Voltage Suppressor (7.5V)
Current output type
Secondary is not allowed to open circuit

Dimension (in mm±0.5) :

