

Characteristic:

Safety lock buckle, easy installation.

Technical index:

- Mounting type: Free hanging (In-Line)
- Material of core: Laminated silicon steel
- Applicable standard: GB20840-2014
- Operating temperature: -25℃ ~ +70℃
- Storage temperature: -40℃ ~ +85℃
- Frequency range: 50Hz-60Hz
- Waterproof grade: IP00
- Dielectric strength: 3.5KV 50Hz 1min(enclosure/output)

Electrical parameters:The following parameters are typical values. The actual values shall be subject to the actual measurement of the product

Product picture printing is for reference only, subject to the actual product



Rated input	100		200		300		400		500		600		A	Cable specification: 0.5mm² black and white parallel lines Cable length:100cm~105cm (k) white (l) black TVS Transient voltage suppressor(7.5V) Current output type Secondary is not allowed to open circuit
Rated output	50	100	50	100	50	100	50	100	50	100	50	100	mA	
Turns ratio	1:2000	1:1000	1:4000	1:2000	1:6000	1:3000	1:8000	1:4000	1:10000	1:5000	1:12000	1:6000	—	
Sampling resistance	20	10	20	10	20	10	20	10	20	10	20	10	Ω	
Accuracy	1												%	
Weight	473												g	

Dimensions (in mm±0.5) :

