

SCT024TS (5A output type)



Characteristic:

Safety lock buckle, easy installation, screw terminal output.

Product picture printing is for reference only,
subject to the actual product

Technical index:

Mounting type:Free hanging (In-Line)
Material of core: Laminated silicon steel
Applicable standard:: GB20840-2014
Operating temperature: -25℃ ~ +60℃
Storage temperature: -30℃ ~ +90℃
Frequency range: 50Hz-60Hz
Waterproof grade: IP00
Dielectric strength: 3.5KV 50Hz 1min



Electrical parameters:The following parameters are typical values. The
actual values shall be subject to the actual measurement of the product

Rated input	100A		150A		200A		250A		300A		400A	
Rated output	5A		5A		5A		5A		5A		5A	
Turns ratio	1: 20		1: 30		1: 40		1: 50		1: 60		1: 80	
Accuracy	0.5%	1%	0.5%	1%	0.5%	1%	0.5%	1%	0.5%	1%	0.5%	1%
Power	0.1VA	0.5VA	0.1VA	0.5VA	1VA	2.5VA	1VA	2.5VA	1VA	2.5VA	1VA	2.5VA
Weight	204g											

Current output type
Secondary is not allowed to open circuit

Dimension (in mm±0.5) :

