

Characteristic:

Safety lock buckle, easy installation, cable output.


Product picture :(the printed words are for reference only, subject to the actual product)

Technical index:

- Mounting type: Free hanging (In-Line)
- Material of core: Ferrite
- Applicable standards: GB20840-2014
- Operating temperature: -25℃ ~ +60℃
- Storage temperature: -30℃ ~ +90℃
- Frequency range: 50Hz-1KHz
- Dielectric strength: Input (bare conductor)/Output AC 800V/1min 50Hz
- Output/housing AC 3.5KV/1min 50Hz



Electrical parameters: ( The following parameters are typical values and actual values will be subject to product testing )

|              |             |    |    |    |    |    |      |                                                                                                                                                                                                                                                                                             |
|--------------|-------------|----|----|----|----|----|------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Rated input  | 10          | 20 | 30 | 50 | 60 | 80 | A    | <div>Specifications of cable:<br/>0.3mm² black and white twisted pair<br/>The length of cable: 50cm~55cm</div> <div></div> <div>Voltage output type<br/>Secondary is not allowed to short circuit</div> |
| Rated output | 0.333/1/3/5 |    |    |    |    |    | V/AC |                                                                                                                                                                                                                                                                                             |
| Accuracy     | 0.5/1       |    |    |    |    |    | %    |                                                                                                                                                                                                                                                                                             |
| Phase shift  | ≤184'       |    |    |    |    |    | '    |                                                                                                                                                                                                                                                                                             |
| Weight       | 45          |    |    |    |    |    | g    |                                                                                                                                                                                                                                                                                             |

Dimensions ( in mm±0.5 ) :

