

Characteristic:

Safety lock buckle, easy installation, cable output.

Product picture :(the printed words are for reference only, subject to the actual product)

Technical index:

- Mounting type:Free hanging (In-Line)
- Material of core: Ferrite
- Applicable standards: GB20840-2014
- Operating temperature: -25℃ ~+60℃
- Storage temperature: -30℃ ~+90℃
- Frequency range: 50Hz-1KHz
- Waterproof grade: IP00
- Dielectric strength: Input (bare conductor)/Output AC 800V/1min 50Hz
- Output/housing AC 3.5KV/1min 50Hz



Electrical parameters: (The following parameters are typical values and actual values will be subject to product testing)

Rated input	20		50			60	80			A	Specifications of cable: 0.3mm² black and white twisted pair The length of cable: 50cm~55cm TVS: Transient Voltage Suppressor (7.5V) Current output type Secondary is not allowed to open circuit
Rated output	20	10	50	25	16.6	20	80	40	26.6	mA	
Turns ratio	1:1000	1:2000	1:1000	1:2000	1:3000	1:3000	1:1000	1:2000	1:3000	-	
Accuracy	0.5	0.5/0.2	0.5	0.5/0.2	0.5/0.2	0.5/0.2	0.5	0.5/0.2	0.5/0.2	%	
Sampling resistance	10									Ω	
Phase shift	≤184'									'	
Weight	45									g	

Dimensions (in mm±0.5):

