

### Characteristics:

Safety lock buckle, easy installation, cable output.

Product picture printing is for reference only, subject to the actual product

### Technical index:

Mounting type: Free hanging (In-Line)

Material of core: Ferrite

Applicable standards: GB20840-2014

Operating temperature: -25 °C ~ +60 °C

Storage temperature: -30 °C ~ +90 °C

Frequency range: 50Hz-1KHz

Dielectric strength: Input (bare conductor)/Output AC 800V/1min 50Hz

Output/housing AC 3.5KV/1min 50Hz



Electrical parameters: The following parameters are typical values. The actual values shall be subject to the actual measurement of the product

Rated input	1	5				10			20		A
Rated output	1	2.5	5	10	5	10	20	20	25	mA	
Turns ratio	1:1000	1:2000	1:1000	1:500	1:2000	1:1000	1:500	1:1000	1:800	-	
Sampling resistance	5	10	5	5	10	5	5	5	5	Ω	
Accuracy	1										%
Weight	25										g

Specifications of cable:  
 2 x 0.2mm<sup>2</sup> two core sheathed wire  
 The length of cable: 100cm~105cm

TVS: Transient Voltage Suppressor (7.5V)  
 Current output type  
 Secondary is not allowed to open circuit

### Dimensions (in:mm±0.5):





