

Characteristic:

Safety lock buckle, easy installation, cable output.

Product picture printing is for reference only, subject to the actual product

Technical index:

Mounting type: Free hanging (In-Line)

Material of core: Laminated silicon steel

Applicable standards: GB20840-2014

Operating temperature: $-25^{\circ}\text{C} \sim +60^{\circ}\text{C}$

Storage temperature: $-30^{\circ}\text{C} \sim +90^{\circ}\text{C}$

Frequency range: 50Hz-60Hz

Dielectric strength: Input (bare conductor)/Output AC 800V/1min 50Hz

Output/housing AC 3.5KV/1min 50Hz



Electrical parameters: The following parameters are typical values. The actual values shall be subject to the actual measurement of the product

Rated input	50		100		200			300		400			A
Rated output	50	100	50	100	20	50	100	50	100	50	80	100	mA
Turns ratio	1:1000	1:500	1:2000	1:1000	1:10000	1:4000	1:1000	1:6000	1:3000	1:8000	1:5000	1:4000	-
Sampling resistance	20	10	20	10	50	20	10	20	10	20	20	8	Ω
Accuracy	1												%
Weight	226												g

Specifications of cable:
 2 x 0.2mm² two core sheathed cable
 The length of cable: 100cm~105cm

TVS: Transient Voltage Suppressor (7.5V)
 Current output type
 Secondary is not allowed to open circuit

Dimensions (in: mm ± 0.5):

