

Characteristic:

Safety lock buckle, easy installation, cable output.

Product picture printing is for reference only,
subject to the actual product

Technical index:

Mounting type:Free hanging (In-Line)
Material of core: Laminated silicon steel
Applicable standard:: GB20840-2014
Operating temperature: -25℃ ~ +60℃
Storage temperature: -30℃ ~ +90℃
Frequency range: 50Hz-60Hz
Dielectric strength: Input (bare conductor)/Output AC 800V/1min 50Hz
Output/housingAC 3.5KV/1min 50Hz

Electrical parameters:The following parameters are typical values. The
actual values shall be subject to the actual measurement of the product



Rated input	50		100		200			300		400			A
Rated output	50	100	50	100	20	50	100	50	100	50	80	100	mA
Turns ratio	1:1000	1:500	1:2000	1:1000	1:10000	1:4000	1:1000	1:6000	1:3000	1:8000	1:5000	1:4000	—
Sampling resistance	20	10	20	10	50	20	10	20	10	20	20	8	Ω
Accuracy	1												%
Weight	226												g

Specifications of cable:
0.3mm² black and white twisted pair
The length of cable: 50cm~55cm

TVS: Transient Voltage Suppressor (7.5V)
Current output type
Secondary is not allowed to open circuit

Dimension (in mm±0.5) :

