

Characteristics:

Safety lock buckle, easy installation,cable output.

Product picture printing is for reference only,
subject to the actual product

Technical index :

Mounting type: Free hanging (In-Line)

Material of core: Ferrite

Applicable standards: GB20840-2014

Operating temperature: -25℃ ~ +60℃

Storage temperature: -30℃ ~ +90℃

Frequency range: 50Hz-1KHz

Waterproof grade: IP00

Dielectric strength: Input (bare conductor)/Output AC 800V/1min 50Hz

Output/housing AC 3.5KV/1min 50Hz



Electrical parameters:The following parameters are typical values. The
actual values shall be subject to the actual measurement of the product

Rated input	1	5			10			20		A
Rated output	1	2.5	5	10	5	10	20	20	25	mA
Turns ratio	1:1000	1:2000	1:1000	1:500	1:2000	1:1000	1:500	1:1000	1:800	—
Sampling resistance	5	10	5	5	10	5	5	5	5	Ω
Accuracy	1	0.5	0.5	1	0.5	0.5	1	1	1	%
Weight	25									g

Specifications of cable:
2 x 0.2mm² two core sheathed wire
The length of cable: 100cm~105cm

(k) white
(1) Red

TVS: Transient Voltage Suppressor (7.5V)
Current output type
Secondary is not allowed to open circuit

Dimensions (in:mm±0.5):





