

Characteristic:

Safety lock buckle, easy installation,cable output.


Product picture printing is for reference only,
subject to the actual product

Technical index:

Mounting type:Free hanging (In-Line)
Material of core: Laminated silicon steel
Applicable standards: GB20840-2014
Operating temperature: -25℃ ~ +60℃
Storage temperature: -30℃ ~ +90℃
Frequency range: 50Hz-60Hz
Waterproof grade: IP00
Dielectric strength: Input (bare conductor)/Output AC 800V/1min 50Hz
Output/housing AC 3.5KV/1min 50Hz



Electrical parameters:The following parameters are typical values. The
actual values shall be subject to the actual measurement of the product

Rated input	50		100		200			300		400			A	Specifications of cable: 2 x 0.2mm² two core sheathed cable The length of cable:100cm~105cm  TVS: Transient Voltage Suppressor (7.5V) Current output type Secondary is not allowed to open circuit
Rated output	50	100	50	100	20	50	100	50	100	50	80	100	mA	
Turns ratio	1:1000	1:500	1:2000	1:1000	1:10000	1:4000	1:1000	1:6000	1:3000	1:8000	1:5000	1:4000	—	
Accuracy	0.5	1	0.5/0.2	0.5	0.5/0.2	0.5/0.2	0.5	0.5/0.2	0.5/0.2	0.5/0.2	0.5/0.2	0.5/0.2	%	
Sampling resistance	20	10	20	10	50	20	10	20	10	20	20	8	Ω	
Weight	226												g	

Dimensions (in:mm±0.5):

