

Characteristic:

Safety lock buckle, easy installation, cable output.


Product picture printing is for reference only,
subject to the actual product

Technical index:

- Mounting type:Free hanging (In-Line)
Material of core: Laminated silicon steel
Applicable standards: GB20840-2014
Operating temperature: -25℃ ~ +60℃
Storage temperature: -30℃ ~ +90℃
Frequency range: 50Hz-60Hz
Waterproof grade: IP00
Dielectric strength: Input (bare conductor)/Output AC 800V/1min 50Hz
Output/housingAC 3.5KV/1min 50Hz



Electrical parameters:The following parameters are typical values. The
actual values shall be subject to the actual measurement of the product

Rated input	100A		150A		200A		250A		300A		400A		Specifications of cable: 1mm² black and white twisted pair. The length of cable: 100cm~105cm  Current output type Secondary is not allowed to open circuit
Rated output	5A		5A		5A		5A		5A		5A		
Turns ratio	1： 20		1： 30		1： 40		1： 50		1： 60		1： 80		
Accuracy	0. 5%	1%	0. 5%	1%	0. 5%	1%	0. 5%	1%	0. 5%	1%	0. 5%	1%	
Power	0. 1VA	0. 5VA	0. 1VA	0. 5VA	1VA	2. 5VA	1VA	2. 5VA	1VA	2. 5VA	1VA	2. 5VA	
Weight	226g												

Dimension (in mm±0.5) :

