

PE2816-M



Characteristics:

1. Vacuum epoxy resin encapsulated, 100℃ /6 hours high temperature aging, long working life 20 years and with high dielectric strength
2. High quality H18 laminated silicon steel, low temperature rise, high efficiency
3. PBT engineering plastic, environmental protection, flame retardant, 120 degrees no deformation
4. Reasonable structure, convenient installation, low noise, strong seismic, sealed waterproof, moisture-proof



Technical index:

Mounting type: PCB

Flame resistance : UL94-V0

Insulation class: B

Operation temperature: -30℃~+70℃

Work frequency: 50Hz~60Hz

Dielectric strength: Pri/Sec. 3.75KV 50Hz 1min 5mA, Sec/Sec 500V 50Hz 1min 5mA

Electrical parameters: (The following parameters are typical values and actual values will be subject to product testing)


Primary voltage	110/220/230/380	V
Primary voltage range	±10	%
Voltage regulation	≤29	%
Power	2	VA
Temperature rising	≤13	℃
No-load loss	≤0.39	W
Weight	93.3	g

Standard output parameter table:


(Factory test is based on the full-load voltage)

Secondary voltage		Secondary no-load voltage		Secondary full-load current	
Single	Double	Single	Double	Single	Double
6V	2×6V	8.5V	2×8V	333mA	2×167mA
7.5V	2×7.5V	10.6V	2×10V	266mA	2×133mA
9V	2×9V	12.7V	2×12V	222mA	2×111mA
12V	2×12V	16.9V	2×16V	166mA	2×83mA
15V	2×15V	21.2V	2×20V	133mA	2×67mA
18V	2×18V	25.4V	2×24V	111mA	2×56mA
24V	2×24V	33.8V	2×32V	83mA	2×42mA


Schematic diagram:




Dimension (in mm±0.5) :



Front view




Bottom view




PCB location instance

Package




30 PCS/box



8 boxes/carton



44 cartons/pallet



Package	Each one	About 93.3g	1 pcs
	Each box	About 2.9Kg	30 pcs
	Each carton	About 23.7Kg	240 pcs
	Each pallet	About 1054.8Kg	10560 pcs

Note: The above packaging (large volume) is for reference only, the actual packaging is subject to production and delivery.